

# M2-PC (TG)

11th Generation Intel® Core™ Processors



### Dimension

- L-Version: Length x Width x Height: 390 x 253 x 58 mm
- M-Version: Length x Width x Height: 317 x 253 x 58 mm
- Weight L-Version: 7 kg ± 10%
- Weight M-Version: 6,8 kg ± 10%

### Housing

- Cooler: Aluminium, RAL 9005 powder coated
- Cover electronics: Steel, RAL 9005 powder coated

<b>System</b>	Processor	11th Generation Intel® Core™ Processors Intel® Core™ i7-1185GRE, 4 Cores, 12M Cache, 1.80 GHz up to 4.40 GHz Intel® Core™ i5-1145GRE, 4 Cores, 8M Cache, 1.50 GHz up to 4.10 GHz	
	Memory	Up to 64GB, Dual channel DDR4 up to 3200MHz	
	Storage	1 x M.2 SSD up to 1TB or SATA3.0/PCIe Gen3 x4 NVMe 2 x SSD up to 2TB RAID 0/1/5	
<b>Graphics</b>	Controller	Intel® Iris® Xe Graphics for i7/i5 Processors	
	Feature	OpenGL 4.5, DirectX 12, OpenCL 2.1 HW Decode: WMV9, AVC/H264, JPEG/MJPEG, HEVC/H265, VP9, AV1 HW Encode: AVC/H264, JPEG, HEVC/H265, VP9	
	Triple Displays	Intern + DP++ + HDMI	
<b>Expansion</b>	Interface	1 x PCIe x4 (Gen3 x4) Low Profile	
<b>Rear I/O</b>	Ethernet	3 x GbE (RJ-45)	Optional up to 5 x GbE
	USB	4 x USB 3.1 Gen2 (Type-A) 1 x USB 4.0 Type-C (Thunderbolt 3) (Support USB 3.1 Gen2, DP 1.4)	Optional up to 9 x USB
	Display	1 x DP++ 1 x HDMI	
	Audio		Optional 1 x Line-out, 1 x Mix-in
	Serial		Optional up to 4 x COM (RS232 or 422/485)
<b>Optional (M2 CB)</b>	Controller	M2 Controller Board	
	Feature	1 x Internal Alarm-Buzzer 1 x Out for ext. Alarm-Buzzer 1 x Potentiometer In, 2 x Push Button In 2 x Out for Status LED	
<b>Watchdog Timer</b>	Output & Interval	System Reset, Programmable via Software from 1 to 255 Seconds	
<b>Security</b>	TPM	dTPM 2.0/fTPM (Opt.)	
<b>Power Options</b>	DC	24 VDC	
	AC	230/115 VAC (50/60Hz)	
	DCAC	24 VDC + 230/115 VAC (redundant)	
<b>OS Support</b>	Microsoft/ Linux	Windows 10 Linux	
	<b>Environment</b>	Operating Temp.	-15 to +55°C
	Storage Temp.	-20 to +70°C	
	IP Rating	IP20	
<b>Compass Safe Distance</b>	Standard Compass	- TBD -	
	Steering Compass	- TBD -	
<b>Type Approval</b>		In progress, expected Q2/2022	
		DNV, EU RO MR; Tested according to EN 60945	



Options and additional features are configurable. Contact your Sonove sales representative for further information.  
Depending on the product configuration, interfaces or slot brackets may differ from the figures in this document.

# M2-PC-L (TG)

11th Generation Intel® Core™ Processors



## Drawings




Copyright © 2021, Sonove GmbH/1.4.1

# M2-PC-M (TG)

11th Generation Intel® Core™ Processors



## Drawings



Sonove GmbH  
Hindelanger Str. 33  
87527 Sonthofen  
Deutschland

Tel. +49 8321 67466 200  
Fax +49 8321 67466 199  
marine@sonove.com